

The **EB1000** Industrial Generator From Honda

10000 watts of industrial strength, portable power that's rugged, reliable, and designed for the demands of the construction and rental industries. **New CO-MINDER™ advanced carbon monoxide detection system** continuously measures CO levels and automatically shuts down the generator before detected CO levels near the generator become dangerously high.*



FEATURES

- **10000 watts** (83.8/41.7A) 120/240V
- **Powerful, reliable Honda GX630 V-Twin engine**
- **DAVR (Digital Auto Voltage Regulation)**
- **GFCI/neutral bond protection**
- **CO-MINDER™** automatically shuts down the generator if it detects carbon monoxide gas reaching unsafe levels
- **Electric start** (battery included) makes starting easy, along with recoil back-up
- **Standard wheel kit with folding handles and hanger kit**
- **i-Monitor** LCD readout for performance monitoring and diagnostics
- Protected by **Oil Alert®**
- **USDA-qualified spark arrestor/muffler**
- **Long run time**
- **Lowest noise level** in its class
- **Easy access** automotive style oil gauge and filler cap
- **Honda 3-Year Residential Warranty/ Honda 3-Year Commercial Warranty†**



SPECIFICATIONS

EB1000

Engine	Honda GX630
Displacement	688cc
Max AC Output	10000w max. 120/240V (83.8/41.7A)
Rated AC Output	9000w rated (75/37.5A)
Receptacles	20A 125V GFCI Duplex (2) 30A 125V Locking Plug 30A 125/250V Locking Plug 50A 125/250V Locking Plug
Voltage Regulation	DAVR
Starting System	Electric
Fuel Tank Capacity	8.19 gal
Run Time Per Tankful	5.4 hours at rated load 7.9 hours at 1/2 load
Noise Level**	73 dB(A) at rated load 71 dB(A) at 1/2 load
Dimensions (L x W x H)	41.0" x 27.7" x 35.1"††
Dry Weight	403 lbs.
USDA Spark Arrestor	Standard
CO-MINDER™	Standard



Find out more at gen.honda.com.

*This product complies with the ANSI/PGMA G300-2018 standard. †Warranty applies to all Honda GX Series Engines and GX Series-powered Honda Power Equipment, 100cc or larger, purchased or put into rental service since January 1, 2010. Exceptions apply. See full warranty details at honda.com. Does not apply to EU1000 models. **Tested in accordance with ISO 9614-2, sound pressure level calculated at 23 Feet (7 meters) using the front plane of the generator (control panel side) per ASHRAE Handbook 2017. ††Including hanging hook and with handles folded. Please read the owner's manual before operating your Honda Power Equipment and never use in a closed or partly enclosed area where you could be exposed to odorless, poisonous carbon monoxide. Connection of a generator to house power requires a transfer device to avoid possible injury to power company personnel. Consult a qualified electrician. © 2020 American Honda Motor Co., Inc. C1022